



Insert Part Number		3732-2GMTW
Military Specification		MS51830-101
Reference Number		KNCA0256J
Insert Type		Miniature
Internal Thread Form		UNJC
Internal Thread Size		2-56
External Thread Size		8-32
External Thread Length	inch	0.090
Nominal Length Q	inch	0.120
Insert Material		Stainless Steel - 303 CRES
Insert Finish		Passivated
Insert Coating		-

Loksert solid keylocking inserts are an easily installed thread assembly that are ideal for replacing damaged or worn threads in virtually any material - ferrous, non-ferrous and non-metallic.

They are constructed from high quality carbon steel or extremely hard wearing stainless steel. One piece Loksert inserts are supplied with the dove-tailed locking keys pre-assembled. The pre-positioned keys automatically position the insert at the correct depth below the surface of the parent material. Lokserts are suitable for repairing and creating threads in a wide range of applications including forgings and castings and are especially suited to situations that experience heavy wear and vibration - such as mining, construction and earthmoving equipment.

COMPATIBLE LOKSERT INSTALLATION AND REMOVAL TOOLS	
TOOL TYPE	Part #
Hand Installation tool - Miniature	3732-2GMTWT
Hand Installation tool - Thin Wall	-
Hand Installation tool - Heavy Duty	-
Hand Installation tool - Universal (TW & HD)	-
Hand Installation tool - Extra Heavy Duty	-
Hand Installation tool - Solid	-
Pneumatic Front End Assembly (FEA)	-
Pneumatic Tool	-

powercoil.com.au

PowerCoil and Loksert are registered trademarks of Bordo International Pty Ltd Australia





DRILLED HOLE DIMENSIONS INTERMEDIATE/PLUG TAP

A Tapping Drill Size	mm	3.4
A Tapping Drill Size	inch	0.134
Tapping Drill Part Number		




TAPPED HOLE DIMENSIONS

Tap Size		8-32
Tap Tolerance		2B
T Tapping Depth minimum	mm	-
T Tapping Depth minimum	inch	0.140
Loksert Tap Part Number	Intermediate	3732-8GI
C Countersink Width minimum	mm	-
C Countersink Width minimum	inch	0.166




INSERT SPECIFICATIONS

Internal Thread		2-56
Internal Thread Tolerance		UNCJ-3B
External Thread		8-32
External Thread Tolerance		UNC-3A
Q Nominal Length	inch	0.120
Locking Keys	#	2



INSERT REMOVAL SPECIFICATIONS

R1 Drill Size	mm	-
R1 Drill Size	inch	#33
R2 Drill Depth minimum	mm	-
R2 Drill Depth minimum	inch	1/16



IMPORTANT The success of any drilling and tapping operation is dependant upon many factors -type of material being cut, cutting speed, coolant, equipment being used - and it is not possible to give specific drill sizes for each material. Drill sizes shown are recommendations only and Bordo International would strongly suggest that independent testing be performed for specific and critical applications.

For detailed removal instructions please visit powercoil.com.au